OJ Drives® OJ DV GEN II

DV-3015

ECODESIGN Specification EN 61800-9-2 : 2023




Drive data

Part number		DV-3015
Product name	Motor drive	s for ventilation
Nominal apparent power		3.9 kVA
Nominal rated output power		1.6 kW
Nominal output current		4.5 Arms
Maximum operation temperature		50.0 °C
Input frequency		50.0 Hz
Voltage		3 x 400 VAC
Standby loss		2.7 W

Power losses in % of rated apparent output power

Frequency	Current	Relative loss	Efficiency
0%	25%	0.6%	63.0%
0%	50%	0.8%	70.0%
0%	100%	1.1%	76.2%
50%	25%	0.6%	92.7%
50%	50%	0.8%	94.3%
50%	100%	1.1%	95.3%
90%	25%	0.5%	96.2%
90%	50%	0.8%	96.6%
90%	100%	1.5%	96.2%
100%	25%	0.7%	95.8%
100%	50%	0.8%	96.9%
100%	100%	1.1%	97.7%

0% are measured at minimum frequency 10%



DV-3015 part Load point

OJ ELECTRONICS

OJ cannot be held liable for any errors the material. OJ reserves the right to alter its products without notice. This also applies to products already on order, provided that such alterations can be made without requiring subsequent changes in specifications already agreed. The contents of this material may be subject to copyright and other intellectual property rights and is either the property of or used under license by OJ Electronics. The OJ trademark is a registered trademark of OJ Electronics A/S.